

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
9 December 2004 (09.12.2004)

PCT

(10) International Publication Number
WO 2004/105999 A1

(51) International Patent Classification⁷: B24B 9/16, B23K 26/00, B28D 5/00

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(21) International Application Number: PCT/IN2003/000245

(22) International Filing Date: 18 July 2003 (18.07.2003)

(25) Filing Language: English

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(26) Publication Language: English

(30) Priority Data: 550/MUM/2003 30 May 2003 (30.05.2003) IN

Published:

- with international search report
- with amended claims


(71) Applicant and

(72) Inventor: PATEL, Arvindbhai, Lavjibhai [IN/IN]; 48/A, Arvind Estate, Bapunagar, Ahmedabad 380 025 (IN).

(74) Agent: ACHARYA, Rajeshkumar; H. K. Acharya & Company, M/2, N.R. House, Near Popular House, Ashram Road, Ahmedabad 380 009 (IN).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A NOVEL LASER BRUTING MACHINE



(57) Abstract: A Novel Laser Bruting machine consists of mainly three sections (i) Diamond Holder (8) (ii) Set up device (3) & (iii) Processing device (4). Diamond holder (8) consists of rough diamond (5), stitching die (6) & magnetic die (7). Also the rough diamond stone to be centered and bruted is stitched on top of stitching die (6) by adhesive & heat. The stitching die (6) is then fixed on top of the magnetic die (7). Setup device (3) consist of CNC interface & video system. The diamond which is to be centered and hence diamond holder is put vertically on motorized rotatable platform (11). After completion of centering the diamond the diamond holder is carried to processing device & fixed horizontally on motorized rotatable platform (23) of processing device (4). Processing device consist of CNC Interface, Heat Exchanger (25), Video system, Beam delivery mechanism (26), Laser source (27), RF-Q Switch driver (28), Power supply (29) & stabilizer. Beam delivery mechanism of processing device consists of (i) Bruting process system and (ii) Girdle polishing system. With the standard software computer suggest an optimal cut to have accurate rounded shape of the diamond taking dimensions & shape into account.

WO 2004/105999 A1